

FG-Serie										
Modell	VdS	Nenn-Spannung V	Nenn-Kapazität (C20) Ah	Abmessungen				Gewicht g	Anschlüsse	Info
				Länge mm	Breite mm	Höhe mm	Höhe über Kontakte mm			
FG10121		6	1,2	97	24,5	50,5	55	300	FASTON 4,8	
FG10301		6	3,0	134	30,0	60,0	65	680	FASTON 4,8	
FG10381		6	3,8	66	33,0	118,0	124	750	FASTON 4,8	
FG10451		6	4,5	70	48,0	102,0	106	890	FASTON 4,8	
FG10721		6	7,2	151	34,0	94,0	98	1380	FASTON 4,8	
FG11201	x	6	12,0	151	50,0	94,0	99	2100	FASTON 4,8	
FG11202	x	6	12,0	151	50,0	94,0	99	2100	FASTON 6,3	
FG20086		12	0,8	96	25,0	61,5	61,5	360	Kabel mit Stecker	
FG20121	x	12	1,2	97	48,5	50,5	55	580	FASTON 4,8	
FG20121A		12	1,2	97	42,0	51,0	55	550	FASTON 4,8	
FG20201	x	12	2,0	178	34,0	60,0	65	890	FASTON 4,8	
FG20271		12	2,7	79	55,5	102,0	106	1100	FASTON 4,8	
FG20301		12	3,0	134	68,0	61,0	65	1300	FASTON 4,8	
FG20451		12	4,5	90	70,0	102,0	106	1750	FASTON 4,8	
FG20721	x	12	7,2	151	65,0	94,0	99	2650	FASTON 4,8	
FG20722	x	12	7,2	151	65,0	94,0	99	2650	FASTON 6,3	
FG21201	x	12	12,0	151	98,0	94,0	99	4200	FASTON 4,8	
FG21202	x	12	12,0	151	98,0	94,0	99	4200	FASTON 6,3	
FG21503	x	12	15,0	181	76,0	167,0	167	6100	Bolzen	
FG21803	x	12	18,0	181	76,0	167,0	167	6200	Bolzen	
FG22703	x	12	27,0	166	175,0	125,0	125	9000	Bolzen	
FG23504	x	12	35,0	198	133,0	165,0	175	10400	Innengewinde M5	
FG24204	x	12	42,0	196	163,0	174,0	174	15000	Innengewinde M5	
FG26504	x	12	65,0	271	166,0	190,0	190	22600	Innengewinde M6	
FG27004	x	12	70,0	350	163,0	174,0	174	24000	Innengewinde M6	
FG2A007	x	12	100,0	329	172,0	214,0	221	34000	Innengewinde M6	