

Grundtyp - 10-Jahres-Batterien

Typ	Nennspannung V	Nennkapazität 20h Ah	Abmessungen				Gewicht ca. kg	Standardanschlüsse oder Verbindungen	Info
			Länge mm	Breite mm	Höhe mm	Gesamthöhe (inkl. Anschlüssen) mm			
LC-T122P	12	2,0	177,0	23,9	60,0	64,0	0,64	Faston Typ 187	
LC-T122PU	12	2,0	177,0	23,9	60,0	64,0	0,64	Faston Typ 187	
LC-TA122P	12	2,0	182,0	23,9	61,7	61,7	0,64	Druckkontakt	
LC-TA122PU	12	2,0	182,0	23,9	61,7	61,7	0,64	Druckkontakt	
LC-P066R5P	6	6,5	151,0	34,0	94,0	100,0	1,2	Faston Typ 187 oder 250	
LC-P067R2P	6	7,2	151,0	34,0	94,0	100,0	1,3	Faston Typ 187 oder 250	
LC-P0610P	6	10,0	151,0	50,0	94,0	100,0	1,8	Faston Typ 187 oder 250	
LG-P0612P	6	12,0	151,0	50,0	94,0	100,0	2,0	Faston Typ 187 oder 250	
LC-P126R5P	12	6,5	151,0	64,5	94,0	100,0	2,3	Faston Typ 187 oder 250	
LC-P127R2P	12	7,2	151,0	64,5	94,0	100,0	2,5	Faston Typ 187 oder 250	
LC-P1215P	12	15,0	181,0	76,0	167,0	167,0	6,0	Faston Typ 250	
LC-P1224P	12	24,0	166,0	175,0	150,0	150,0	11,0	M5 Schraubstecker	
LC-P1238P	12	38,0	197,0	166,0	200,0	200,0	16,0	M6 Schraubstecker	
LC-P1265P	12	65,0	350,0	166,0	175,0	175,0	25,0	M6 Schraubstecker	
LC-X1275P	12	75,0	304,0	171,0	200,0	236,0	26,0	M6 Schraubbolzen	
LC-X12100P	12	100,0	407,0	173,0	210,0	246,0	36,0	M8 Schraubbolzen	
LC-P067R2P	6	7,2	151,0	34,0	94,0	100,0	1,3	Faston Typ 187 oder 250	
LC-P127R2P	12	7,2	151,0	64,5	94,0	100,0	2,5	Faston Typ 187 oder 250	
LC-P0612P	6	12,0	151,0	50,0	94,0	100,0	2,0	Faston Typ 187 oder 250	
LC-X1224AP	12	24,0	165,0	125,0	175,0	175,0	9,0	M5 Schraubstecker	
LC-X1224P	12	24,0	165,0	125,0	175,0	179,5	9,0	M5 Schraubbolzen	
LC-X1228AP	12	28,0	165,0	125,0	175,0	175,0	11,0	M5 Schraubstecker	
LC-X1228P	12	28,0	165,0	125,0	175,0	179,5	11,0	M5 Schraubbolzen	
LC-X1238AP	12	38,0	197,0	165,0	175,0	175,0	13,0	M5 Schraubstecker	
LC-X1238P	12	38,0	197,0	165,0	175,0	180,0	13,0	M6 Schraubbolzen	
LC-X1242AP	12	42,0	197,0	165,0	175,0	175,0	16,0	M6 Schraubstecker	
LC-X1224P	12	42,0	197,0	165,0	175,0	180,0	16,0	M6 Schraubstecker	
LC-X1265P	12	65,0	350,0	166,0	175,0	175,0	20,0	M6 Schraubstecker	
LC-XA12100P	12	100,0	407,0	173,0	210,0	236,0	33,0	M8 Schraubstecker	