

Grundtyp - 5-Jahres- Batterie									
Typ	Nenn-Spannung V	Nenn-Kapazität C20 Ah	Abmessungen				Gewicht ca. kg	Standard-anschlüsse oder Verbindungen	Info
			Länge mm	Breite mm	Höhe mm	Gesamthöhe (inkl. Anschlüssen) mm			
LC-R061 R3PG	6	1,3	97,0	24,0	50,0	55,0	0,30	FASTON Typ 187	
LC-R061 R3PU	6	1,3	97,0	24,0	50,0	55,0	0,30	FASTON Typ 187	
LC-R063R2PG	6	3,2	66,0	33,0	119,0	125,0	0,66	FASTON Typ 187	
LC-R063R4PG	6	3,4	134,0	34,0	60,0	66,0	0,62	FASTON Typ 187	
LC-R063R4PU	6	3,4	134,0	34,0	60,0	66,0	0,62	FASTON Typ 187	
LC-RB064PG	6	4,0	70,0	47,0	102,0	108,0	0,90	FASTON Typ 187 oder 250	
LC-R065PG	6	5,0	70,0	47,0	102,0	108,0	0,97	FASTON Typ 187 oder 250	
LC-R065P	6	5,0	70,0	47,0	102,0	108,0	0,97	FASTON Typ 187 oder 250	
LC-RB066R5PG	6	6,5	151,0	34,0	94,0	100,0	1,16	FASTON Typ 187 oder 250	
LC-R067R2PG	6	7,2	151,0	34,0	94,0	100,0	1,26	FASTON Typ 187 oder 250	
LC-R067R2P	6	7,2	151,0	34,0	94,0	100,0	1,26	FASTON Typ 187 oder 250	
LC-RB0610PG	6	10,0	151,0	50,0	94,0	100,0	1,78	FASTON Typ 187 oder 250	
LC-R0612PG	6	12,0	151,0	50,0	94,0	100,0	195,00	FASTON Typ 187 oder 250	
LC-R0612P	6	12,0	151,0	50,0	94,0	100,0	195,00	FASTON Typ 187 oder 250	
LC-R1212P	6	12,0	151,0	101,5	94,0	100,0	390,00	FASTON Typ 187 oder 250	
LC-R121R3PG	12	1,3	97,0	47,5	50,0	55,0	0,59	FASTON Typ 187	
LC-R121R3PU	12	1,3	97,0	47,5	50,0	55,0	0,59	FASTON Typ 187	
LC-R122R2PG	12	2,2	177,0	34,0	60,0	66,0	0,80	FASTON Typ 187	
LC-R122R2PU	12	2,2	177,0	34,0	60,0	66,0	0,80	FASTON Typ 187	
LC-R123R4PG	12	3,4	134,0	67,0	60,0	66,0	1,20	FASTON Typ 187	
LC-R123R4PU	12	3,4	134,0	67,0	60,0	66,0	1,2	FASTON Typ 187	
LC-13B124PG	12	4,0	90,0	70,0	102,0	108,0	1,74	FASTON Typ 187 oder 250	
LC-R125PG	12	5,0	90,0	70,0	102,0	108,0	1,93	FASTON Typ 187 oder 250	
LC-R125P	12	5,0	90,0	70,0	102,0	108,0	1,93	FASTON Typ 187 oder 250	
LC-R129P1	12	9,0	151,0	64,5	94,0	102,0	2,55	FASTON Typ 187 oder 250	
LC-RB064P	6	4,0	70,0	47,0	102,0	108,0	0,9	FASTON Typ 187 oder 250	
LC-RB064R2P	6	4,2	70,0	47,0	102,0	108,0	0,78	FASTON Typ 187 oder 250	
LC-RB124P	12	4,0	909,0	70,0	102,0	108,0	1,74	FASTON Typ 187 oder 250	
LC-RB126R5PG	12	6,5	151,0	64,5	94,0	100,0	2,27	FASTON Typ 187 oder 250	
LC-R127R2PG	12	7,2	151,0	64,5	94,0	100,0	2,47	FASTON Typ 187 oder 250	
LC-R127R2P	12	7,2	151,0	64,5	94,0	100,0	2,47	FASTON Typ 187 oder 250	
LC-RB1210PG	12	10,0	151,0	101,0	94,0	102,0	3,5	FASTON Typ 187 oder 250	
LC-R1212PG	12	12,0	151,0	101,5	94,0	102,0	3,9	FASTON Typ 187 oder 250	
LC-RC1217PG	12	17,0	181,0	76,0	167,0	167,0	6,5	M5 Schraubbolzen	
LC-RC1217P	12	17,0	181,0	76,0	167,0	167,0	6,5	M5 Schraubbolzen	
LC-L1224PG	12	24,0	165,0	125,0	175,0	175,0	709	M5 Schraubbolzen	