

Yuasa Serie NP - Allgemein-Anwendungen												
Batterie-Typ	FR	Nenn-Spannung V	Kapazität C20 Ah	Kapazität C10 Ah	Abmessungen			Gewicht kg	Poltyp	VDS-Nr.	Info	
					Länge mm	Breite mm	Höhe* mm					
NP3-4	x	4	3,0	2,8	90,5	34,0	64,0	0,42	Flach 4,8mm	-		
NP4.2-4H	x	4	4,4	4,2	47,8	35,5	119,0	0,56	Flach 4,8mm	-		
NP10-4	x	4	10,0	9,2	102,0	50,0	98,0	1,35	Flach 6,3mm	-		
NP1-6	x	6	1,0	0,9	51,0	42,5	54,5	0,25	Flach 4,8mm	-		
NP1.2-6	x	6	1,2	1,1	97,0	25,0	54,5	0,31	Flach 4,8mm	-		
NP2.6-6	x	6	2,6	2,4	134,0	34,0	64,0	0,56	Flach 4,8mm	-		
NP2.8-6	x	6	2,8	2,6	134,0	34,0	64,0	0,57	Flach 4,8mm	-		
NP3-6	x	6	3,0	2,8	134,0	34,0	64,0	0,70	Flach 4,8mm	-		
NP4-6	x	6	4,0	3,6	70,0	47,0	105,5	0,85	Flach 4,8mm	-		
NP4-6W	x	6	4,0	3,6	70,0	47,0	102,5	0,85	AMP	-		
NP4.2-6H	x	6	4,4	4,2	48,0	51,5	120,0	0,80	Flach 4,8mm	-		
NP7-6	x	6	7,0	6,5	151,0	34,0	97,5	1,35	Flach 4,8mm	-		
NP10-6	x	6	10,0	9,3	151,0	34,0	97,5	1,93	Flach 4,8mm	G186010		
NP12-6	x	6	12,0	11,2	151,0	34,0	97,5	2,05	Flach 4,8mm	G194006		
NP0.8-12	x	12	0,8	0,7	96,0	25,0	61,5	0,35	JSP	-		
NP1.2-12	x	12	1,2	1,1	97,0	48,0	54,5	0,57	Flach 4,8mm	G195053		
NP1.9-12	x	12	1,9	1,7	178,0	34,0	64,0	0,81	Flach 4,8mm	G189100		
NP2-12	x	12	2,0	1,8	150,0	20,0	89,0	0,70	Flach 4,8mm gerade	-		
NP2.1-12	x	12	2,1	1,9	178,0	34,0	64,0	0,83	Flach 4,8mm	beantragt		
NP2.3-12	x	12	2,3	2,1	178,0	34,0	64,0	0,94	Flach 4,8mm	-		
NP2.6-12	x	12	2,6	2,4	134,0	67,0	64,0	1,10	Flach 4,8mm	G192102		
NP2.8-12	x	12	2,8	2,6	134,0	67,0	64,0	1,10	Flach 4,8mm	-		
NP3.2-12	x	12	3,2	3,0	134,0	67,0	64,0	1,17	Flach 4,8mm	-		
NP4-12	x	12	4,0	3,7	90,0	70,0	106,0	1,57	Flach 4,8mm	-		
NP6-12	x	12	6,0	5,6	151,0	65,0	97,5	2,45	Flach 4,8mm	G183067		
NP7-12	x	12	7,0	6,5	151,0	65,0	97,5	2,65	Flach 4,8mm	G189099		
NP7-12L	x	12	7,0	6,5	151,0	65,0	97,5	2,65	Flach 4,8mm	-		
NP10-12	x	12	10,0	9,3	151,0	101,0	97,5	4,00	Flach 4,8mm	G186101		
NP12-12	x	12	12,0	11,2	151,0	98,0	97,5	4,09	Flach 4,8mm	G189170		
NP17-12I	x	12	17,0	14,0	181,0	76,0	167,0	5,97	Schraubanschluss	G197022		
NP17-12IFR	x	12	17,0	14,0	181,0	76,0	167,0	5,97	Innengewinde M5	-		
NP24-12B	x	12	24,0	22,3	166,0	175,0	125,0	8,92	Schraubanschluss	G182026		
NP24-12	x	12	24,0	22,3	166,0	175,0	125,0	8,92	Innengewinde M5	geplant		
NP38-12	x	12	38,0	35,4	197,0	165,0	170,0	13,93	Schraubanschluss	G182024		
NP38-12I	x	12	38,0	35,4	197,0	165,0	170,0	13,93	Innengewinde M5	G182024		
NP65-12	x	12	65,0	60,5	350,0	166,0	174,0	22,82	Schraubanschluss	G183008		
NP65-12I	x	12	65,0	60,5	350,0	166,0	174,0	22,82	Schraubanschluss	G183008		

\*) Höhe über den Polen