

dryfit A500													
Typen-Bezeichnung	Nenn-Spannung V	Nenn-Kapazität (C20) Ah	Entlade-Strom mA	Maximal-Belastung A	Max.zul. Strom 5 sek. A	Abmessungen				Gewicht ca. kg	Anschlüsse	VdS-Nr.	Info
						Länge mm	Breite mm	Höhe über Deckel mm	Höhe über Kontakte mm				
A502 / 10,0 S	2	10,0	500	80	300	52,9	50,5	94,5	98,4	0,7	Steckanschlüsse 4,8		
A504 / 3,5 S	4	3,5	175	60	300	90,5	34,5	60,5	64,4	0,5	Steckanschlüsse 4,8		
A506 / 1,2 S	6	1,2	60	40	240	97,3	25,5	52,0	55,6	0,3	Steckanschlüsse 4,8		
A506 / 3,5 S	6	3,5	175	60	300	134,5	34,8	60,5	64,4	0,7	Steckanschlüsse 4,8		
A506 / 4,2 S	6	4,2	210	60	300	62,3	52,0	98,0	101,9	0,9	Steckanschlüsse 4,8		
A506 / 4,2 K	6	4,2	210	60	300	62,3	52,0	98,0	98,3	0,9	Druck-Kontakt		
A506 / 6,5 S	6	6,5	325	80	300	152,0	34,5	94,5	98,4	1,3	Steckanschlüsse 4,8		
A506 / 10,0 S	6	10,0	500	80	300	152,0	50,5	94,5	98,4	2,1	Steckanschlüsse 4,8	G 189230	
A508 / 3,5 S	8	3,5	175	60	300	178,5	34,1	60,5	64,4	1,0	Steckanschlüsse 4,8		
A512 / 1,2 S	12	1,2	60	40	240	97,5	49,5	51,0	54,9	0,7	Steckanschlüsse 4,8	G 195088	
A512 / 2,0 S	12	2,0	100	40	240	178,5	34,1	60,5	64,4	1,0	Steckanschlüsse 4,8	G 191016	
A512 / 3,5 S	12	3,5	175	60	300	134,0	66,8	60,0	64,4	1,5	Steckanschlüsse 4,8	G 190045	
A512 / 6,5 S	12	6,5	325	80	300	151,7	65,5	94,5	98,4	2,6	Steckanschlüsse 4,8	G 189023	
A512 / 6,5 SR	12	6,5	325	80	300	151,7	65,5	94,5	98,4	2,6	Steckanschlüsse 4,8		
A512 / 10,0 S	12	10,0	500	80	300	152,0	98,0	94,5	98,4	4,0	Steckanschlüsse 4,8	G 189231	
A512 / 10,0 SR	12	10,0	500	80	300	152,0	98,0	94,5	98,4	4,0	Steckanschlüsse 6,3		
A512 / 16,0 G5	12	16,0	800	200	700	181,0	76,0	152,0	167,0	6,2	Schraubanschl. M5	G 189232	
A512 / 16,0 SR	12	16,0	800	100	300	181,0	76,0	152,0	156,4	6,2	Steckanschlüsse 6,3		
A512 / 24,0 G5	12	24,0	1200	200	800	167,0	176,0	126,0	126,0	9,6	Schraubanschl. M5		
A512 / 25,0 G5	12	25,0	1250	200	800	167,0	176,0	126,0	126,0	9,6	Schraubanschl. M5	G 196025	
A512 / 30,0 G6	12	30,0	150	400	1500	197,0	132,0	160,0	184,0	11,3	Schraubanschl. M6	G 191047	
A512 / 40,0 A	12	40,0	2000	400	1500	210,0	175,0	175,0	175,0	15,0	Konuspol	G 191015	
A512 / 40,0 G6	12	40,0	2000	400	1500	210,0	175,0	175,0	175,0	15,0	Schraubanschl. M6	G 191015	
A512 / 55,0 A	12	55,0	2750	400	1500	261,0	135,0	208,0	230,0	19,0	Konuspol		
A512 / 60,0 A	12	60,0	3000	400	1500	306,0	175,0	190,0	190,0	21,8	Konuspol		
A512 / 60,0 AS	12	60,0	3000	400	1500	281,0	175,0	190,0	190,0	21,8	Konuspol		
A512 / 60,0 G6	12	60,0	3000	400	1500	306,0	175,0	190,0	190,0	21,8	Schraubanschl. M6		
A512 / 60,0 G6S	12	60,0	3000	400	1500	281,0	175,0	190,0	190,0	21,8	Schraubanschl. M6		
A512 / 65,0 A	12	65,0	3250	440	1500	381,0	175,0	190,0	190,0	24,4	Konuspol		
A512 / 65,0 G6	12	65,0	3250	440	1500	381,0	175,0	190,0	190,0	24,4	Schraubanschl. M6		
A512 / 85,0 A	12	85,0	4250	600	2600	330,0	171,0	214,0	235,5	32,6	Konuspol	G 190046	
A512 / 115,0 A	12	115,0	5750	770	2600	284,0	267,0	208,0	230,0	40,3	Konuspol		
A512 / 120,0 A	12	120,0	6000	770	2600	513,0	189,0	195,0	223,0	41,0	A-Terminal		
A512 / 140,0 A	12	140,0	7000	770	2600	513,0	223,0	195,0	223,0	48,0	A-Terminal		
A512 / 200,0 A	12	200,0	10000	770	2600	518,0	274,0	216,0	238,0	70,0	A-Terminal		

Kontaktarten:	Konuspol nach DIN EN 60 095 T2
	G = Schraubanschluss
	SR = Steckkontakt
	S = Steckkontakt