

TWICELL (NiMH-Akkus)

Modell	Spannung V	Kapazität mAh		Gewicht g	Abmaße mm		Bauform	Info
		min.	typ.		Ø	Höhe		
HR-3U(2300)	1.2	2100	2300	30.0	14.3	50.4	AA	
HR-3U(1700)	1.2	1600	1700	27.0	14.2	50.0	AA	
HR-4U	1.2	740	800	13.0	10.5	44.5	AAA	
HR-AAAU	1.2	650	730	13.0	10.5	44.5	AAA	
HR-5/4AAAU	1.2	760	850	15.0	10.5	50.0	5/4 AAA	
HR-5/3AAAU	1.2	920	1000	19.0	10.5	67.5	5/3 AAA	
HR-AAU	1.2	1500	1650	28.0	14.2	50.0	AA	
HR-AAC	1.2	950	1000	27.0	14.2	50.0	AA	
HR-AAUL	1.2	1300	1450	27.0	14.2	49.0	(AA)	
HR-4/5AUC	1.2	1550	1700	35.0	17.0	43.0	4/5 A	
HR-4/5AU	1.2	1900	2150	35.0	17.0	43.0	4/5 A	
HR-AU	1.2	2450	2700	40.0	17.0	50.0	A	
HR-4/3AU	1.2	3600	4000	55.0	17.0	67.5	4/3A	
HR-4/3FAU	1.2	4100	4500	62.0	18.0	67.5	(4/3 A)	
HR-4/3FAUC	1.2	3300	3700	62.0	18.0	67.5	(4/3A)	
HR-SC	1.2	2300	2600	58.0	23.0	43.5	SC	
HR-SCU	1.2	2700	3000	61.0	23.0	43.5	SC	
HR-SCC	1.2	1900	2100	59.0	23.0	43.0	SC	
HR-D	1.2	6500	7300	172.0	34.0	59.3	D	
HR-AUC	1.2	1900	2100	40.0	17.0	50.0	A	
HR-4/3FAUP (360)	1.2	3400	3600	58.0	18.1	67.0	4/3FA	
HR-4/5AAU	1.2	1300	1350	24.0	14.5	43.0	4/5AA	
HR-2/3AAAUC	1.2	350	400	9.0	10.5	30.0	2/3AA	
HR-4/5AAUC	1.2	1000	1100	23.0	14.2	43.0	4/5AA	
HR-4UC	1.2	600	650	13.0	10.5	44.5	AAA	
HR-4/5SCU	1.2	1900	2100	47.0	23.0	33.5	4/5SC	
HR-4/5FAUP	1.2	1800	1950	39.0	18.1	43.2	4/5FA	
HR-4/3FAUP (320)	1.2	3050	3200	60.0	18.1	67.0	4/3FA	
HR-4/3AAUP	1.2	1800	2000	36.0	14.2	67.0	4/3AA	
HR-AA	1.2	1000	1100	27.0	14.2	50.0	AA	
HR-DU	1.2	8450	9000	178.0	34.0	59.3	D	